



Quality Wood Finishing Products



HIGH BUILD WATERBORNE FINISH

NO EYE BURN · NO NOSE BURN · SELF SEAL

PRODUCT DESCRIPTION

Woodwright Eco-Var is a high build, alkyd modified polyurethane, self-crosslinking varnish. Expect fantastic vertical hang and attractive grain enhancement characteristics with Eco-Var. It is a true high-end performance coating with excellent chemical resilience. This water-borne varnish is resistant to scratching, marring and moisture. It can be used as both a sealer and topcoat. One Product, Two Coats, That's It! Economically priced. As with other Woodwright finishes, this varnish has an extremely silky feel ensuring your furniture and cabinetry's superior quality. 5040 Eco-Var is ideal for doors, trim packages and flooring. It has a viscosity that is ready to spray from the can. Eco-Var's environmentally friendly formula requires that it contain **NO HAPS** and **Very Low VOC**.

PHYSICAL PROPERTIES

Type:	Alkyd Modified Polyurethane	<u>Air Dry & Durability Schedule</u>	
V.O.C.:	.75 lb/gal.	To Touch:	20—30 minutes
Weight/gal:	8.40 + or—0.15	To Sand:	30—45 minutes
Viscosity:	56—59 sec. Zahn #2 @ 77 F	To Recoat:	30—60 minutes
Sheens:	10, 20, 35, 45, 90	To Pack:	8—12 hours @ 75F
Weight Solids:	39% + or - 1%	Solvent / Water Resist	7 days
Volume Solids:	34% + or - 1%	Full Cure	30 days
Optimum Coverage:	571 sq. ft./gal @ 1 mil dry (no loss)		

APPLICATION

Method:	Spray airless or air assisted (Stainless Steel Equipment Required)
Reducer:	May be thinned with distilled water if necessary.
Substrate:	Wood (Stained if desired), clean and dust free
No. of Coats:	Two—Sealer and Topcoat (an additional coat at no more than 3.5 mils wet may be applied, if desired)
Shelf Life:	1 Year, stored airtight. (DO NOT FREEZE)

David E Easterday & Company, Inc.
Wilmot, Ohio 44689
1.800.322.8172 · woodwrightfinish.com