

# MATERIAL SAFETY DATA SHEET

844-1352 CHROMA-CHEM®BURNT UMBER

BU



Material no.		Version	1.34 / US
Specification	139837	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	1 / 12

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product information

Trade name : 844-1352 CHROMA-CHEM®BURNT UMBER BU  
Use of the Substance / Preparation : Non-aqueous colorant  
Manufactured by Evonik

Company : Evonik Degussa Corporation  
379 Interpace Parkway  
Parsippany, NJ 07054  
USA

Telephone : 973-541-8000  
Telefax : 973-541-8040

US: CHEMTREC EMERGENCY NUMBER : 800-424-9300

CANADA: CANUTEC EMERGENCY NUMBER : 613-996-6666

Product Regulatory Services : 973-541-8060

## 2. HAZARDS IDENTIFICATION

### \*\*\* EMERGENCY OVERVIEW \*\*\*

**Form-paste**    **Color-brown**    **Odor-Sweet ether-like odor.**

May cause eye, skin and respiratory tract irritation.  
Combustible liquid and vapor.

### POTENTIAL HEALTH EFFECTS

#### Eye contact

Irritating.  
May injure eye tissue if not removed promptly.  
May cause conjunctivitis.

#### Skin Contact

A moderate skin irritant based on testing of similar CHROMA-CHEM® base mixtures. Prolonged or repeated contact may cause irritation.  
Prolonged skin contact with large amounts of ether acetates may cause drowsiness.

#### Inhalation

Possibly irritating.  
Excessive inhalation of solvent vapors may cause nasal and respiratory irritation and central

**MATERIAL SAFETY DATA SHEET****844-1352 CHROMA-CHEM®BURNT UMBER****BU**

Material no.		Version	<b>1.34 / US</b>
Specification	<b>139837</b>	Revision date	<b>10/31/2008</b>
Order Number		Print Date	<b>11/01/2008</b>
		Page	<b>2 / 12</b>

nervous system effects including dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even death.

**Ingestion**

May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

**Chronic Health Hazard**

High vapor concentrations (3000 ppm) of propylene glycol monomethyl ether acetate caused upper respiratory irritation and liver and kidney effects in subchronic animal testing. The relevance of these results to humans is not known.

Prolonged inhalation of iron oxide dust is known to produce a condition known as siderosis. On X-rays it appears to be a benign pneumoconiosis and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis producing materials such as silica. Overexposure to crystalline silica dust causes lung effects. There is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica (IARC 1, OSHA).

Crystalline Silica has been assigned the A2 carcinogen designation by ACGIH, suspected human carcinogen.

Repeated inhalation of crystalline silica may cause kidney disease, auto-immune disease, and lymph node effects.

Manganese dioxide dust has caused developmental effects in the absence of maternal effects.

Repeated exposure to manganese dioxide may lead to neurological effects and lung effects.

Because this product is a free-flowing liquid or paste, dust inhalation is not an expected route of exposure.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Information on ingredients / Hazardous components**

2-methoxy-1-methylethyl acetate				
CAS-No.	108-65-6	Percent (Wt./ Wt.)	10 - 30 %	
Iron oxide				
CAS-No.	1332-37-2	Percent (Wt./ Wt.)	10 - 30 %	
Aluminum oxide				
CAS-No.	1344-28-1	Percent (Wt./ Wt.)	5 - 10 %	
manganese dioxide				
CAS-No.	1313-13-9	Percent (Wt./ Wt.)	5 - 10 %	
NJTSR No.56705700001-5384P				
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	5 - 10 %	
Silica, crystalline (quartz)				
CAS-No.	14808-60-7	Percent (Wt./ Wt.)	1 - 5 %	
NJTSR No.56705700001-5055P				
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	1 - 5 %	

**Other information**

This material is classified as hazardous under OSHA regulations.

## MATERIAL SAFETY DATA SHEET

844-1352 CHROMA-CHEM®BURNT UMBER

BU



Material no.		Version	1.34 / US
Specification	139837	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	3 / 12

### 4. FIRST AID MEASURES

#### Inhalation

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If unconscious, evaluate the need for artificial respiration. Get immediate medical attention.

#### Skin contact

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Obtain medical attention. Wash clothing before reuse. Destroy or thoroughly clean contaminated shoes before reuse.

#### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 30 minutes, while holding eyelids apart.

Do not allow contaminated water to contact the unaffected eye or face during irrigation of an affected eye.

Obtain medical attention immediately.

#### Ingestion

Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

If the heart has stopped or breathing has stopped, trained personnel should begin cardiopulmonary resuscitation or artificial respiration immediately.

### 5. FIRE-FIGHTING MEASURES

Flash point 46.67 °C , 116 °F  
Method: Setaflash Closed Cup

OSHA Flammability Classification Combustible Liquid

#### Suitable extinguishing media

Use water spray or fog, foam, dry chemical or CO<sub>2</sub>.

#### Specific hazards during fire fighting

Combustible liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.

#### Further information

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear. Containers can build up pressure if exposed to heat (fire). Cool with water spray.

# MATERIAL SAFETY DATA SHEET

844-1352 CHROMA-CHEM®BURNT UMBER

BU



Material no.		Version	1.34 / US
Specification	139837	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	4 / 12

## 6. ACCIDENTAL RELEASE MEASURES

### Additional advice

Absorb spill with inert material, then place in a chemical waste container. After removal, flush contaminated area with water and collect for disposal. Clean up spills immediately. Remove sources of ignition and ventilate area. Use a respirator and other protective equipment as outlined in Section 8. Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

## 7. HANDLING AND STORAGE

### Handling

#### Safe handling advice

Keep away from heat. Keep away from sparks, flames and other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use with adequate ventilation. The need for grounding and bonding of containers in accordance with OSHA 29 CFR 1910.106 and NFPA 77 should be assessed for all product transfers. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.

### Storage

#### Requirements for storage areas and containers

Keep in a dry, cool place.  
Keep container closed when not in use.  
Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Component occupational exposure guidelines

#### • Aluminum oxide

CAS-No.	1344-28-1	
Control parameters	5 mg/m3 Respirable fraction.	PEL:(OSHA Z1)
	15 mg/m3 Total dust.	PEL:(OSHA Z1)
	10 mg/m3 Total dust.	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):(US CA OEL)
	5 mg/m3 Respirable fraction.	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):(US CA OEL)
	1 mg/m3	Time Weighted Average (TWA):(ACGIH)

**MATERIAL SAFETY DATA SHEET****844-1352 CHROMA-CHEM®BURNT UMBER****BU**

Material no.		Version	<b>1.34 / US</b>
Specification	<b>139837</b>	Revision date	<b>10/31/2008</b>
Order Number		Print Date	<b>11/01/2008</b>
		Page	<b>5 / 12</b>

Respirable fraction.

**• Silica, crystalline (quartz)**

CAS-No.	14808-60-7	
	0.05 mg/m3	Time Weighted Average (TWA):(ACGIH)
	Respirable particles.	
	0.1 mg/m3	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):(US CA OEL)
	Respirable dust.	
	0.3 mg/m3	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):(US CA OEL)
	Total dust.	
	2.4millions of particles per cubic foot of air Respirable.	Time Weighted Average (TWA):(Z3)
	The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.	
	0.1 mg/m3	Time Weighted Average (TWA):(Z3)
	Respirable.	
	The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.	
	0.3 mg/m3	Time Weighted Average (TWA):(Z3)
	Total dust.	
	The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower values of % SiO <sub>2</sub> will give higher exposure limits.	
	0.025 mg/m3	Time Weighted Average (TWA):(ACGIH)
	Respirable fraction.	

**• Iron oxide**

CAS-No.	1332-37-2	(Z3)
	Respirable fraction. Listed.	
	5 mg/m3 Respirable fraction.	PEL:(OSHA Z1)
	15 mg/m3 Total dust.	PEL:(OSHA Z1)
	3 mg/m3 Respirable particles.	Time Weighted Average (TWA):(ACGIH)
	10 mg/m3	Time Weighted Average (TWA):(ACGIH)

# MATERIAL SAFETY DATA SHEET

844-1352 CHROMA-CHEM®BURNT UMBER

BU



Material no.		Version	1.34 / US
Specification	139837	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	6 / 12

Inhalable particles.

- **manganese dioxide**

CAS-No.	1313-13-9	Ceiling Limit Value:(OSHA Z1)
	5 mg/m <sup>3</sup> as Mn	Time Weighted Average (TWA)
	0.2 mg/m <sup>3</sup> as Mn	Permissible Exposure Limit (PEL):(US CA OEL)
	0.2 mg/m <sup>3</sup> as Mn	Time Weighted Average (TWA):(ACGIH)

### Other information

The AIHA WEEL for propylene glycol monomethyl ether acetate is 50 ppm TWA.  
The exposure limit for iron oxide is for dust and fume as Fe.  
The exposure value for crystalline silica is for the respirable fraction.

### Engineering measures

Use explosion-proof ventilation equipment.

### Personal protective equipment

#### Respiratory protection

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

#### Hand protection

Use impermeable gloves.

#### Eye protection

Chemical resistant goggles must be worn.

#### Skin and body protection

A safety shower and eye wash fountain should be readily available.  
To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

Form	paste
Color	brown
Odor	Sweet ether-like odor.

### Safety data

Boiling point/range	> 143 °C
Flash point	46.67 °C Method: Setaflash Closed Cup
Relative density	1.5

# MATERIAL SAFETY DATA SHEET

844-1352 CHROMA-CHEM®BURNT UMBER

BU



Material no.		Version	1.34 / US
Specification	139837	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	7 / 12

Solubility/qualitative	Solubility in water: Negligible.	
Viscosity, dynamic	90 - 110 KU (25 °C)	
Solvents and Volatiles Data	% VOC (gm/l)	537.38
Evaporation rate	Slower than butyl acetate	

## 10. STABILITY AND REACTIVITY

Conditions to avoid	Avoid high temperatures and sources of ignition.
Materials to avoid	oxidizing substances
Hazardous decomposition products	Exothermic reactions of aluminum oxide above 200°C with halocarbon vapors produces toxic HCl and phosgene.

## 11. TOXICOLOGICAL INFORMATION

Component Acute oral toxicity	2-methoxy-1-methylethyl acetate 108-65-6 LD50 Rat: 8532 mg/kg
	Iron oxide 1332-37-2 LD50 Rat: > 5000 mg/kg
	Aluminum oxide 1344-28-1 LD50 Rat: > 10000 mg/kg
	NJTSR No.56705700001-5384P Trade Secret LD50 Rat: > 2000 mg/kg
Component Acute inhalation toxicity	LC50 (rat) > 4345 ppm, 6 hours, vapor related to substance: 2-methoxy-1-methylethyl acetate
Component Acute dermal toxicity	2-methoxy-1-methylethyl acetate 108-65-6 LD50 Rabbit: > 19000 mg/kg (calculated) (literature value)
Component carcinogenicity assessment	Silica, crystalline (quartz) 14808-60-7 Contains a component which is classified as an IARC Group 1 carcinogen

# MATERIAL SAFETY DATA SHEET

844-1352 CHROMA-CHEM®BURNT UMBER

BU



Material no.		Version	1.34 / US
Specification	139837	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	8 / 12

(carcinogenic to humans).

Component General Toxicity  
Information

2-methoxy-1-methylethyl acetate  
108-65-6

High vapor concentrations (3000 ppm) of propylene glycol monomethyl ether acetate caused upper respiratory irritation and liver and kidney effects in subchronic animal testing. The relevance of these results to humans is not known.

manganese dioxide  
1313-13-9

Repeated exposure to manganese dioxide may cause lung effects. There is conclusive evidence that inhaling high levels of manganese dioxide may lead to neurological effects in humans, such as altered gait, tremor, and psychiatric disturbances. These effects may continue to progress even after exposure to manganese dioxide ceases. Manganese dioxide dust has caused developmental toxicity in the absence of maternal effects.

Silica, crystalline (quartz)  
14808-60-7

Chronic inhalation of crystalline silica dust may cause kidney disease, auto-immune disease, and lymph node effects in humans. Crystalline silica has shown positive results in "in vitro" screening tests for mutagenicity.

---

## 12. ECOLOGICAL INFORMATION

General Ecological Information No ecotoxicological studies are available.

---

## 13. DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL

Advice on disposal

Waste must be disposed of in accordance with federal, state, provincial and local regulations. CONTAINER DISPOSAL: Empty containers by removing the top and inverting to allow all free-flowing product to drain. To meet regulatory criteria, the container is considered empty when less than 3% remains in the container. Additional special handling is not typically required and the empty container can be discarded with other non-hazardous trash. Note: Local disposal regulations may be more stringent and require additional restrictions or precautions. Customers should check with their local disposal company, municipal or state authority. Recycle of plastic or metal containers may require clean rather than empty containers. In this case the containers can be rinsed with mineral spirits until the containers are considered generally product free.



**MATERIAL SAFETY DATA SHEET****844-1352 CHROMA-CHEM®BURNT UMBER****BU**

Material no.		Version	<b>1.34 / US</b>
Specification	<b>139837</b>	Revision date	<b>10/31/2008</b>
Order Number		Print Date	<b>11/01/2008</b>
		Page	<b>9 / 12</b>

**14. TRANSPORT INFORMATION****Sea transport IMDG-Code**

Class	3
UN-No	1263
Packaging group	III
EmS	F-E, S-E

Proper technical name (Proper shipping name)  
PAINT RELATED MATERIAL

**Air transport ICAO-TI/IATA-DGR**

Class	3
UN-No	1263
Packaging group	III

Proper technical name (Proper shipping name)  
Paint related material

**Loading instructions/Remarks**

IATA_C	ERG-Code 3L
IATA_P	ERG-Code 3L
CFR_INWTR	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.
CFR_RAIL	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.
CFR_ROAD	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.

**15. REGULATORY INFORMATION****Information on ingredients / Non-hazardous components**

This product contains the following non-hazardous components

NJTSR No.56705700001-6864P			
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	10 - 30 %

**US Federal Regulations****OSHA**

If listed below, chemical specific standards apply to the product or components:

- None listed

# MATERIAL SAFETY DATA SHEET

844-1352 CHROMA-CHEM®BURNT UMBER

BU



Material no.		Version	1.34 / US
Specification	139837	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	10 / 12

## Clean Air Act Section (112)

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- manganese dioxide  
CAS-No. 1313-13-9

## CERCLA Reportable Quantities

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- None listed

## SARA Title III Section 311/312 Hazard Categories

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard
- Chronic Health Hazard
- Fire Hazard

## SARA Title III Section 313 Reportable Substances

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- Aluminum oxide  
CAS-No. 1344-28-1
- manganese dioxide  
CAS-No. 1313-13-9

## Toxic Substances Control Act (TSCA)

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

- None listed

## Other US Federal Regulatory Information

Note: Silica, crystalline (airborne particles of respirable size) is listed as a carcinogen under California Proposition 65. However, the physical form of this product (a free flowing paste) precludes exposure to airborne particles of respirable size.

## State Regulations

### California Proposition 65

A warning under the California Drinking Water Act is required only if listed below:

WARNING! This product contains a chemical known in the State of California to cause cancer.

- Silica, crystalline (quartz)

# MATERIAL SAFETY DATA SHEET

**844-1352 CHROMA-CHEM®BURNT UMBER**

**BU**



Material no.		Version	<b>1.34 / US</b>
Specification	<b>139837</b>	Revision date	<b>10/31/2008</b>
Order Number		Print Date	<b>11/01/2008</b>
		Page	<b>11 / 12</b>

CAS-No. 14808-60-7

## International Chemical Inventory Status

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact the Product Regulatory Services Department.

- |                          |                           |
|--------------------------|---------------------------|
| • Europe (EINECS/ELINCS) | Listed/registered         |
| • USA (TSCA)             | Listed/registered         |
| • Canada (DSL)           | Listed/registered         |
| • Australia (AICS)       | Not listed/Not registered |
| • Japan (MITI)           | Not listed/Not registered |
| • Korea (TCCL)           | Listed/registered         |
| • Philippines (PICCS)    | Not listed/Not registered |
| • China                  | Listed/registered         |

---

## 16. OTHER INFORMATION

### HMIS Ratings

Health :	2*
Flammability :	2
Physical Hazard :	0

### Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# MATERIAL SAFETY DATA SHEET

**844-1352 CHROMA-CHEM®BURNT UMBER**

**BU**



Material no.		Version	<b>1.34 / US</b>
Specification	<b>139837</b>	Revision date	<b>10/31/2008</b>
Order Number		Print Date	<b>11/01/2008</b>
		Page	<b>12 / 12</b>

.  
.