



Quality Wood Finishing Products

9930 **E7**

CATALYZED VARNISH

EXTREMELY LOW ODOR * ULTRA LOW HAPS * EXTENDED POT LIFE * WATER WHITE

PRODUCT DESCRIPTION

WOODWRIGHT E7 IS A HIGH BUILD, MODIFIED COCONUT ALKYD CATALYZED VARNISH WITH ATTRACTIVE GRAIN ENHANCING CHARACTERISTICS. IT HAS EXTREMELY LOW ODOR AND MINIMAL EYE & NOSE IRRITATION. THIS PRODUCT CONTAINS LOW HAPS AND VERY LOW VOC. **E7** IS A TRUE HIGH END PERFORMANCE COATING WITH EXCELLENT RESISTANCE TO SCRATCHING, MARRING, MOISTURE AND CHEMICALS. **E7** PROVIDES A GREAT VALUE BY BEING COMPETITIVELY PRICED AND HAVING AN EXTENDED POT-LIFE (WHICH YIELDS VIRTUALLY NO WASTE). THE RESINS SELECTED FOR THIS PRODUCT PROVIDE A CLEAR, WATER WHITE FINISH. AS WITH ALL WOODWRIGHT FINISHES, THIS VARNISH HAS A SILKY FEEL ADDING TO YOUR FURNITURE OR CABINETRY'S QUALITY. **E7** REQUIRES ONLY 4OZ. OF CATALYST PER GALLON AND IS AT A VISCOSITY THAT IS READY TO SPRAY FROM THE CAN. THIS PROVIDES EASE OF APPLICATION AND NO LOSS OF SOLIDS DUE TO THINNING OR A HIGH RATIO OF CATALYST. **E7** CAN BE USED OVER ANY WOODWRIGHT CATALYZED SEALER BUT CAN BE USED AS A SELF-SEAL PRODUCT, AS WELL.

PHYSICAL PROPERTIES

TYPE:	MODIFIED COCONUT ALKYD	AIR DRY SCHEDULE W/ 4OZ. CATALYST PER GALLON:
V.O.C.:	4.24 LB/GAL. (NO H2O)	TO TOUCH: 20-30 MINUTES
WEIGHT/GAL.:	7.9 LB + OR – 0.15	TO SAND: 60 MINUTES
VISCOSITY:	24.50-25.50 SEC. ZAHN #2 EZ @ 77 F.	TO RECOAT: 60 MINUTES
SHEENS:	5, 20, 35, 45, 60, 90	TO PACK: 8 HOURS
WEIGHT SOLIDS:	37% + OR – 1%	
VOLUME SOLIDS:	32% + OR – 1%	

APPLICATION

METHOD:	SPRAY, AIRLESS OR AIR ASSISTED (STAINLESS STEEL EQUIPMENT REQUIRED)
REDUCER:	WOODWRIGHT TH2910 LACQUER THINNER OR TH7100 FLOSOL, IF DESIRED
SUBSTRATE:	WOOD (STAINED IF DESIRED), CLEAN AND DUST FREE
CATALYST:	WOODWRIGHT 35260 CATALYST (4OZ. PER GALLON)
POT LIFE:	UP TO 48 HOURS @ 77 DEG. F. (SEALED AIRTIGHT)
SHELF LIFE:	1YEAR (UNOPENED)