



Quality Wood Finishing Products

9935



LOW ODOR · LOW HAPS · EXTENDED POT LIFE

#### PRODUCT DESCRIPTION

WOODWRIGHT E7 ADVANCE SEALER IS A HIGH BUILD, NON-YELLOWING, COCONUT ALKYD CATALYZED SEALER WITH FAST DRY AND EXCEPTIONAL SANDABILITY. IT HAS AN EXTREMELY LOW ODOR AND HAPS CONTENT. 9935 SEALER IS A TRUE HIGH END PERFORMANCE SEALER. COMPETITIVELY PRICED, WITH AN EXTENDED POT-LIFE (WHICH YIELDS VIRTUALLY NO WASTE), 9935 SEALER PROVIDES A GREAT VALUE. THE RESINS SELECTED FOR THIS PRODUCT PROVIDE AN EXTREMELY CLEAR, NON-YELLOWING FILM MAKING IT IDEAL FOR USE IN WHITE FINISH SYSTEMS. E7 ADVANCE SEALER REQUIRES ONLY 4OZ. OF CATALYST PER GALLON AND IS AT A VISCOSITY THAT IS READY TO SPRAY FROM THE CAN, PROVIDING EASY APPLICATION AND NO LOSS OF SOLIDS DUE TO THINNING OR A HIGH RATIO OF CATALYST.

#### PHYSICAL PROPERTIES

TYPE:	MODIFIED COCONUT ALKYD	AIR DRY SCHEDULE W/ 4OZ. CATALYST PER GALLON:
V.O.C.:	4.44 LB/GAL. (NO H <sub>2</sub> O)	TO TOUCH: 20—25 MINUTES
WEIGHT/GAL.:	7.7 LB + OR - 0.15	TO SAND: 45—60 MINUTES
VISCOSITY:	26-27 SEC. ZAHN #2 EZ @ 77 F.	TO RECOAT: 45—60 MINUTES
VOLUME SOLIDS:	32% + OR - 1%	

#### APPLICATION

METHOD:	SPRAY, AIRLESS OR AIR ASSISTED (STAINLESS STEEL EQUIPMENT REQUIRED)
REDUCER:	WOODWRIGHT TH2910 LACQUER THINNER OR TH7100 FLOSOL, IF DESIRED
SUBSTRATE:	WOOD (STAINED IF DESIRED), CLEAN AND DUST FREE
CATALYST:	WOODWRIGHT 35260 CATALYST (4OZ. PER GALLON) ON WOODWRIGHT STAINS
POT LIFE:	UP TO 48 HOURS @ 77°F CATALYZED (SEALED AIRTIGHT)
SHELF LIFE:	1YEAR (UNOPENED)
FOR DARK STAINS:	USE 5 OZ 35260 CATALYST PER GALLON WHEN SPRAYING OVER DARK STAINS THAT ARE NOT WOODWRIGHT BRAND

