

MATERIAL SAFETY DATA SHEET

844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV



Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	1 / 10

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information

Trade name : 844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV
Use of the Substance / Preparation : Non-aqueous colorant
Manufactured by Evonik

Company : Evonik Degussa Corporation
379 Interpace Parkway
Parsippany, NJ 07054
USA

Telephone : 973-541-8000

Telefax : 973-541-8040

US: CHEMTREC EMERGENCY NUMBER : 800-424-9300

CANADA: CANUTEC EMERGENCY NUMBER : 613-996-6666

Product Regulatory Services : 973-541-8060

2. HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***

Form-paste **Color-Purple.** **Odor-Sweet ether-like odor.**

May cause eye, skin and respiratory tract irritation.
Combustible liquid and vapor.

POTENTIAL HEALTH EFFECTS

Eye contact

Severely irritating.
May cause tearing, reddening and/or swelling.
May cause permanent eye injury.

Skin Contact

A moderate skin irritant based on testing of similar CHROMA-CHEM® base mixtures. Prolonged or repeated contact may cause irritation.
Prolonged skin contact with large amounts of ether acetates may cause drowsiness.

Inhalation

Possibly irritating.
Excessive inhalation of solvent vapors may cause nasal and respiratory irritation and central

MATERIAL SAFETY DATA SHEET

844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV



Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	2 / 10

nervous system effects including dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even death.

Ingestion

May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Chronic Health Hazard

High vapor concentrations (3000 ppm) of propylene glycol monomethyl ether acetate caused upper respiratory irritation and liver and kidney effects in subchronic animal testing. The relevance of these results to humans is not known.

Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

Because this product is a free-flowing liquid or paste, dust inhalation is not an expected route of exposure.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Information on ingredients / Hazardous components

2-methoxy-1-methylethyl acetate			
CAS-No.	108-65-6	Percent (Wt./ Wt.)	30 - 60 %
Stoddard solvent; Low boiling point naphtha - unspecified			
CAS-No.	8052-41-3	Percent (Wt./ Wt.)	10 - 30 %
Kaolin			
CAS-No.	1332-58-7	Percent (Wt./ Wt.)	1 - 5 %
NJTSR No.56705700001-5582P			
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	1 - 5 %
Distillates (petroleum), hydrodesulfurized middle; Gasoil - unspecified			
CAS-No.	64742-80-9	Percent (Wt./ Wt.)	1 - 5 %
NJTSR No.56705700001-5018P			
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	1 - 5 %

Other information

This material is classified as hazardous under OSHA regulations.

This product contains no lead, cadmium, mercury or hexavalent chromium which have been intentionally introduced as an element during manufacture or distribution and the sum of the concentration level of lead, cadmium, mercury, or hexavalent chromium incidentally present in this product shall not exceed 100 parts per million by weight.

4. FIRST AID MEASURES

Inhalation

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If unconscious, evaluate the need for artificial respiration. Get immediate medical attention.

MATERIAL SAFETY DATA SHEET

844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV



Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	3 / 10

Skin contact

Remove contaminated clothing/shoes. Flush skin with water. Follow by washing with soap and water. If symptoms develop or persist, obtain medical attention. Wash clothing before reuse.

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 30 minutes, while holding eyelids apart.

Do not allow contaminated water to contact the unaffected eye or face during irrigation of an affected eye.

Consult a physician immediately.

Ingestion

Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

If the heart has stopped or breathing has stopped, trained personnel should begin cardiopulmonary resuscitation or artificial respiration immediately.

Never administer anything by mouth to an individual who rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

Flash point 42.22 °C , 108 °F
Method: Setaflash Closed Cup

OSHA Flammability Classification Combustible Liquid

Suitable extinguishing media

Use water spray or fog, foam, dry chemical or CO₂.

Specific hazards during fire fighting

Combustible liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.

Further information

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear. Containers can build up pressure if exposed to heat (fire). Cool with water spray.

MATERIAL SAFETY DATA SHEET

844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV



Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	4 / 10

6. ACCIDENTAL RELEASE MEASURES

Additional advice

Absorb spill with inert material, then place in a chemical waste container. After removal, flush contaminated area with water and collect for disposal. Clean up spills immediately. Remove sources of ignition and ventilate area. Use a respirator and other protective equipment as outlined in Section 8. Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

7. HANDLING AND STORAGE

Handling

Safe handling advice

Keep away from heat. Keep away from sparks, flames and other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use with adequate ventilation. The need for grounding and bonding of containers in accordance with OSHA 29 CFR 1910.106 and NFPA 77 should be assessed for all product transfers. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.

Storage

Requirements for storage areas and containers

Keep in a dry, cool place.

Keep container closed when not in use.

Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component occupational exposure guidelines

- **Stoddard solvent; Low boiling point naphtha - unspecified**

CAS-No. 8052-41-3

Control parameters 100 ppm
500 ppm
2900 mg/m³
100 ppm
525 mg/m³

Time Weighted Average (TWA):(ACGIH)
PEL:(OSHA Z1)

Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

- **Kaolin**

CAS-No. 1332-58-7

5 mg/m³
Respirable fraction.

PEL:(OSHA Z1)

15 mg/m³
Total dust.

PEL:(OSHA Z1)

2 mg/m³

Time Weighted Average (TWA):(ACGIH)

MATERIAL SAFETY DATA SHEET

844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV



Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	5 / 10

Respirable fraction.

The value is for particulate matter containing no asbestos and <1% crystalline silica.

2 mg/m³

Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

Respirable dust.

Other information

Exposure values for mineral spirits (CAS Nr 8052-41-3) are given as Stoddard solvent.
The AIHA WEEL for propylene glycol monomethyl ether acetate is 50 ppm TWA.

Engineering measures

Use explosion-proof ventilation equipment.

Personal protective equipment

Respiratory protection

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

Hand protection

Use impermeable gloves.

Eye protection

Chemical resistant goggles must be worn.

Skin and body protection

A safety shower and eye wash fountain should be readily available.

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	paste
Color	Purple.
Odor	Sweet ether-like odor.

Safety data

Boiling point/range	> 143 °C
Flash point	42.22 °C Method: Setaflash Closed Cup
Relative density	1 (25 °C)
Solubility/qualitative	Solubility in water: Negligible.

MATERIAL SAFETY DATA SHEET**844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV**

Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	6 / 10

Viscosity, dynamic 70 - 90 KU (25 °C)

Solvents and Volatiles Data

% VOC (gm/l) 580.56

Evaporation rate Slower than butyl acetate

10. STABILITY AND REACTIVITY

Conditions to avoid Avoid high temperatures and sources of ignition.

Materials to avoid oxidizing substances

11. TOXICOLOGICAL INFORMATION

Component Acute oral toxicity

2-methoxy-1-methylethyl acetate
108-65-6
LD50 Rat: 8532 mg/kgStoddard solvent; Low boiling point naphtha - unspecified
8052-41-3
LD50 Rat: > 5000 mg/kgDistillates (petroleum), hydrodesulfurized middle; Gasoil - unspecified
64742-80-9
LD50 Rat: > 5000 mg/kgNJTSR No.56705700001-5018P
Trade Secret
LD50 Rat: 3430 mg/kg

Component Acute inhalation toxicity

LC50 (rat) > 4345 ppm, 6 hours, vapor
related to substance: 2-methoxy-1-methylethyl acetateStoddard solvent; Low boiling point naphtha - unspecified
8052-41-3
LC50 Rat: > 5500 mg/m3 / 4 hDistillates (petroleum), hydrodesulfurized middle; Gasoil - unspecified
64742-80-9
LC50 Rat: 4600 mg/m3 / 4 h

Component Acute dermal toxicity

2-methoxy-1-methylethyl acetate
108-65-6
LD50 Rabbit: > 19000 mg/kg
(calculated)
(literature value)

MATERIAL SAFETY DATA SHEET

844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV



Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	7 / 10

Stoddard solvent; Low boiling point naphtha - unspecified
8052-41-3
LD50 Rabbit: > 3000 mg/kg

Distillates (petroleum), hydrodesulfurized middle; Gasoil - unspecified
64742-80-9
LD50 Rabbit: > 2000 mg/kg

NJTSR No.56705700001-5018P
Trade Secret
LD50 Rabbit: > 2000 mg/kg

Component General Toxicity Information

2-methoxy-1-methylethyl acetate
108-65-6
High vapor concentrations (3000 ppm) of propylene glycol monomethyl ether acetate caused upper respiratory irritation and liver and kidney effects in subchronic animal testing. The relevance of these results to humans is not known.

12. ECOLOGICAL INFORMATION

General Ecological Information No ecotoxicological studies are available.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Advice on disposal

Waste must be disposed of in accordance with federal, state, provincial and local regulations. CONTAINER DISPOSAL: Empty containers by removing the top and inverting to allow all free-flowing product to drain. To meet regulatory criteria, the container is considered empty when less than 3% remains in the container. Additional special handling is not typically required and the empty container can be discarded with other non-hazardous trash. Note: Local disposal regulations may be more stringent and require additional restrictions or precautions. Customers should check with their local disposal company, municipal or state authority. Recycle of plastic or metal containers may require clean rather than empty containers. In this case the containers can be rinsed with mineral spirits until the containers are considered generally product free.

14. TRANSPORT INFORMATION

Sea transport IMDG-Code

Class	3
UN-No	1263
Packaging group	III
EmS	F-E, S-E

MATERIAL SAFETY DATA SHEET**844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV**

Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	8 / 10

Proper technical name (Proper shipping name)

PAINT RELATED MATERIAL

Air transport ICAO-TI/IATA-DGR

Class	3
UN-No	1263
Packaging group	III

Proper technical name (Proper shipping name)

Paint related material

Loading instructions/Remarks

IATA_C	ERG-Code 3L
IATA_P	ERG-Code 3L
CFR_INWTR	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.
CFR_RAIL	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.
CFR_ROAD	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.

15. REGULATORY INFORMATION**Information on ingredients / Non-hazardous components**

This product contains the following non-hazardous components

NJTSR No.56705700001-5579P			
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	10 - 30 %
NJTSR No.56705700001-6864P			
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	10 - 30 %

US Federal Regulations**OSHA**

If listed below, chemical specific standards apply to the product or components:

- None listed

Clean Air Act Section (112)

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- None listed

MATERIAL SAFETY DATA SHEET

844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV



Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	9 / 10

CERCLA Reportable Quantities

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- None listed

SARA Title III Section 311/312 Hazard Categories

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard
- Chronic Health Hazard
- Fire Hazard

SARA Title III Section 313 Reportable Substances

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- None listed

Toxic Substances Control Act (TSCA)

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

- None listed

State Regulations

California Proposition 65

A warning under the California Drinking Water Act is required only if listed below:

- None listed

MATERIAL SAFETY DATA SHEET

844-9451 CHROMA-CHEM® QUINACRIDONE VIOLET QV



Material no.		Version	2.27 / US
Specification	139168	Revision date	10/31/2008
Order Number		Print Date	11/01/2008
		Page	10 / 10

International Chemical Inventory Status

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact the Product Regulatory Services Department.

- | | |
|--------------------------|---------------------------|
| • Europe (EINECS/ELINCS) | Listed/registered |
| • USA (TSCA) | Listed/registered |
| • Canada (DSL) | Listed/registered |
| • Australia (AICS) | Listed/registered |
| • Japan (MITI) | Not listed/Not registered |
| • Korea (TCCL) | Not listed/Not registered |
| • Philippines (PICCS) | Not listed/Not registered |
| • China | Not listed/Not registered |
| • New Zealand | Not listed/Not registered |

16. OTHER INFORMATION

HMIS Ratings

Health :	2
Flammability :	2
Physical Hazard :	0

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.