



QUALITY WOOD FINISHING PRODUCTS

Product Number: 9936

For proper application instruction please refer to
Woodwright's

Product Name: Rapid Seal Elite NF

**"STANDARD STAIN & VARNISH
APPLICATION TECHNIQUE"**

Type: No-Formaldehyde Catalyzed Sealer

Available Sheens: N/A

Physical Properties

RESIN:	MODIFIED COCONUT ALKYD	AIR DRY SCHEDULE W/ 2 OZ CATALYST / GAL:
VOC:	3.47 LB/GAL (NO H2O)	TO TOUCH: 15—20 MIN
WEIGHT:	8.15 LB/GAL (+ OR - 0.15)	TO SAND: 20—40 MIN
VISCOSITY:	27-28 SEC / ZAHN #2 EZ @ 77°F	TO RECOAT: 30—50 MIN
WEIGHT SOLIDS:	38% (+ or - 1%)	
VOLUME SOLIDS:	33% (+ or - 1%)	THICKNESS: DO NOT EXCEED 5 DRY MILS TOTAL

Application

METHOD:	SPRAY—AIRLESS OR AIR-ASSISTED (STAINLESS STEEL EQUIPMENT REQUIRED)
REDUCER:	WOODWRIGHT TH2910 THINNER OR TH3700 SLOW REDUCER, IF DESIRED
SUBSTRATE:	WOOD (STAINED, IF DESIRED) CLEAN AND DUST-FREE
CATALYST:	2 OZ PER GALLON WOODWRIGHT 35260 CATALYST ON WOODWRIGHT STAINS
POT LIFE:	16 HRS @ 77°F (STORED SEALED AND AIRTIGHT)
SHELF LIFE:	1 YEAR UNOPENED
FULL CURE:	30 DAYS

Features & Benefits

Woodwright 9936 Rapid Seal Elite NF sealer is perfect for all shops looking to reduce the odor in their work environment. It contains and produces no formaldehyde, allowing for a very low odor and virtually no eye and nose burn. Its fast dry time and effortless sand will help move production along quickly. Another great attribute of this sealer is its ability to help reduce sand-through on corners. Use together with Woodwright 9938 Armor Var Elite NF, No-Formaldehyde catalyzed topcoat.